



1967

World 's First Electric Fishing Reel Miya Epoch 67/500 Released

1969

Introduced to The USA and Japanese Fishing Tackle Shows

1998

30th Anniversary from our First Electric Fishing Reel NEW COMMAND X-4 Released

2003

World 's First Remote Control Reel CX-4R Released

2004

World 's First Auto Tension Control Installed on CX-9SP Released

2005

The Greatest Reel US-50 PRO&AM Released



SINCE 1967

Miya Epoch was introduced in 1967, as the world's first electric fishing reel.

MADE IN JAPAN



New Addition The COMMAND Z Series Unveiled

2017

50th Anniversary from ou Electric Fishing Reel and Start of Miya Epoch

2019

World's first Electric Linear Drag Miya Epoch R800 Released



Miya Epoch R800
Winding Power 40kg
(Power mode)
MAX Winding Power 75kg
Power Source DC-12V/24V

MiyaEnoch

Miya Epoch has been recognized as a high-quality brand of high-performance electric reels with unequaled power. Not only in Japan but all over the world.



Reel size / W240×H150×D220mm

CZ-9 Export Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
CZ-9 Ex	0408	110kg	75kg	40kg	110m/min	1.4-23A	1:3.18	No.10/1600m No.20/800m No.12/1400m No.30/500m	10	5.2kg
CZ-9 Ex (24V)	0409	TTOKE	110kg	50kg	120m/min	0.9-12A	1.3.16	No.15/900m	10	J.ZNg

The jigging function for CZ-9 is only installed in the export edition.





Reel size / W260×H150×D220mm

CZ-15 Export Edition

OZ TO EXPE										
Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
CZ-15 Ex	0403	110kg	100kg	45kg	110m/min	1.4-23A	1:3.18	No.10/2000m No.20/1000m No.12/1600m No.30/700m	10	5.7kg
CZ-15 Ex	0406	TTORS	110kg	55kg	120m/min	0.9-12A	1.5.16	No.15/1200m No.40/500m	10	J./ Kg

The jigging function for CZ-15 is only installed in the export edition.



Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
CZ-20 Ex	0404	110kg	110kg	50kg	110m/min	1.4-23A	1:2.5	No.10/2000m No.20/1000m No.12/1600m No.30/700m	10	5.9kg
CZ-20 Ex	0407	TTORS	115kg	60kg	120m/min	0.9-12A	1.2.5	No.15/1200m No.40/500m	10	J.3K6

^{*}The COMMAND Z-30 Export Edition (24volt only) is also available. With the largest spool capacity and the high torque in CZ-series.

^{*} The jigging function for CZ-20/30 is only installed in the export edition.









Reel size / W270×H110×D155mm

R800 English Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
R800 En	0802	70kg	75kg	40kg	165m/min	1.4-35A	1:5.0 (Speed mode)	No.5/1200m No.12/500m No.6/1000m No.15/300m	11	2.7kg
R800 En	0803	TUNE	7 5 Kg	(Power mode)	(Speed mode)	0.9-18A	1:1.8 (Power mode)	No.8/800m No.20/200m No.10/600m	''	2.7 Ng

^{*}MC-Board is the same as the Japanese edition, the indication in the LCD panel contains Japanse, attached an explanation for those words in the English instruction manual.





Reel size / W215×H120×D150mm

AT-3S Export Edition

control

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
AT-3S Ex	0253	40kg	55kg	16kg	150m/min	2.6-15A	1:1.92	No.4/900m No.8/550m No.5/800m No.10/450m No.6/700m No.12/350m	10	1.9kg

PAT

COMMAND **AUTO** series

COMMAND AC-3JP English Edition

AC-3JP English Edition is the technical model and installed with various functions in the most compact body. In addition to the main motor, the sub motor can control the drag. The sub motor makes possible the single switching operation called "Auto Clutch Function" (Clutch ON/OFF).











Reel size / W215×H120×D150mm





for AC-3JP En.



Jigging PRO D.C. 12V









Reel size / W215×H120×D150mm

AC-3JP/AC-3JPC English Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
AC-3JPEn	0255	30ka	43kg	16kg	150m/min	2.6-15A	1:1.92	No.4/700m No.8/400m No.5/600m No.10/300m	10	2.1kg
AC-3JPEn	0256	30kg	50kg	24kg	13011/111111	1.3-12A	1.1.52	No.6/500m No.12/200m	10	Z.1NS
AC-3JPCEn	0257	40kg	55kg	16kg	150m/min	2.6-15A	1:1.92	No.4/900m No.8/550m No.5/800m No.10/450m No.6/700m No.12/350m	10	2.1kg

^{*} Instruction manual is Japanese, and attached an explanatory leaflet in English.









Reel size / W250×H120×D150mm

AT-5S Export Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
AT-5S Ex	0272	40kg	64kg	20kg	150m/min	2.6-15A	1:1.92	No.5/1100m No.12/400m No.6/900m No.15/300m No.8/700m No.20/200m No.10/500m	10	2.3kg

PAT





COMMAND AC.5SC Export Edition

Based on the AT-5S, the AC-5SC Export Edition equipped a sub motor for more technical functions. The clutch ON/OFF with a single switching operation called "Auto Clutch Function" is installed, and the "Auto Jigging Function" allows to continuously attract a target, with full automatic jigging control to wind up and bring down your rig.







Reel size / W250×H120×D150mm

AC-5SC Export Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor	Ball Bearing	Weight
AC-5SCEx	0275	40kg	64kg	20kg	150m/min	2.6-15A	1:1.92	No.5/1100m No.6/900m No.8/700m No.10/500m No.20/200m	10	2.4kg

^{*} The description of the model name on the control panel is the same as the AC-5SEx.




^{*}Instruction manual / Control Pannel / Indication in the LCD panel are all Japanese.

LINE

Miya New Deep Sensor is the best PE line for Miya Epoch electric reels which combines high strength and high sensitivity. 5 color coating type and black type are available.

Made in Japan. 100% PE Fiber



Miya New Deep Sensor

No.	No.5	No.6	No.8	No.10	No.12	No.15	No.20
Total length	1800m	1800m	1800m	1800m	1800m	1200m	1200m
	100m×18	100m×18	100m×18	100m×18	100m×18	100m×12	100m×12
Standard strength	24kg	30kg	37kg	41kg	52kg	60kg	80kg
Product Code	2152	2153	2154	2155	2156	2157	2158



Miya New Deep Sensor Black

No.	No.8	No.10	No.12	No.15	No.20	No.30
Total length	1200m	1200m	1800m	1200m	1200m	1200m
	100m×12	100m×12	100m×18	100m×12	100m×12	100m×12
Standard strength	37kg	41 kg	52kg	60kg	80kg	95kg
Product Code	2140	2144	2141	2142	2143	2085

Fishing Gear

Miya Tension Adjuster

Using the tension adjuster, it makes winding line easy with constant tension while winding the PE line onto your reel. Two types of tension adjuster are available. The recommended size of fishing line is over No.4 PE Line.





Power Cord

3m cord inclueded with new reel package.



	Product Code
3m	7010
5m	7009
10m	7008

Serial Cord for 24Volt Reel

Used to connect two 12volt batteries. Only for 24volt model. This item included in 24volt models.



7022

Guard Arm for AC-5SC•AT-5S

To prevent scratches on the body. Can be attached with each model.



7086

Support Plate set

for AC-3JP/JPC+AT-3S+AT-5S+AC-5SC+R800 This item included with new reel package.



7048

Reel Grease

Use on Metal Connector unit and Traverse cam. This item Included with new reel package.



Guard Arm for AC-3JP/3JPC•AT-3S

To prevent scratches to the Reel. Can be attached with each model.



7085

WEB SNS













Func	tion	CZ-9	CZ-15	CZ-20	CZ-30	R800	AT-3S	AC-3JP AC-3JPC	AT-5S	AC-5SC
Auto tension	Auto tension	•	•	•	•		•	•	•	•
control	control	The auto tension	on function auto	matically contr	ols the winding	speed depend	ing on the pulli	ng of the fish.		
Drag	Drag	•	•	•	•					
assist lever	assistlever	Equipped with	a drag assist l	ever which imp	roved operabi	lity.				
Depth memory	Depth Depth	•	•	•	•	•		•		•
Depth stop	memory stop	The depth men	nory function me	emorizes the po	osition for a cer	tain depth rota	tion and stops t	the spool at that	memorized p	osition.
Power			Big	•	•					
handle	Power handle handle	The power har	ndle is a bigger	handle for inc	reased strengt	h.				
Guard	[Guard]	•	•	•	•					
arm	arm	The guard arm	is equipped as	a standard op	tion to prevent	scratches on th	e body.			
Click	(Click)		•	•	•					
sound brake system	(((soundbrake))) system	The sound bra	ke system appli	es a slight brak	e to the spool	and prevents bo	acklash, and in	forms of the hit	by the loud cli	ck sound.
Electric						•				
linear drag	Electric linear drag	Equipped with	an electric leve	r drag lightly r	esponds that di	riven by a sub r	notor.			
Backlight	Backlight					•				
color change	change	The LCD back	light color can	be chosen fror	n 6 colors.					
High speed	High speed						•			
automatic winding	automatic winding	High speed au	tomatic winding	function winds	up at the high	est speed to the	zero stop pos	ition.		
	- A-4	•	•	•	•		•		•	
Jigging	Jigging		en pause then rep ngth, pause time,					ition.		
Auto	. ^							•		•
Jigging	Auto Jigging	The auto jiggin	g function auto	matically repe	ats the Jigging l	by letting the rig	g back out.			
								•		
Chumming	Chumming	The chumming f	unction disperses	bait from a cert	tain shelf with a	jigging motion a	nd automatically	repeats. Then wi	nds up to the z	ero stop positio
CF	((•	● 12V		
CE mark	CE	CE marking inc	dicates that the	product confor	ms to the essen	tial requiremen	ts specified in t	he EU directive	and regulation	s by sector.

MIYAMAE CO., LTD.

1-2-32 Aramoto Higashiosaka-Shi Osaka-Fu 577-0023 JAPAN TEL+81-6-6782-1010 FAX+81-6-6782-1248

Notice: Modification, specification, and design are subject to change without notice.

Details and colors of the images might be different from ones of real products.

All descriptions are as of the issued date March 2022.