
















Function		CZ-9	CZ-15	CZ-20	CZ-30	R800	AT-3S	AC-3JP AC-3JPC	AT-5S	AC-5SC
Auto tension control		●	●	●	●		●	●	●	●
The auto tension function automatically controls the winding speed depending on the pulling of the fish.										
Drag assist lever		●	●	●	●					
Equipped with a drag assist lever which improved operability.										
Depth memory Depth stop	 	●	●	●	●	●		●		●
The depth memory function memorizes the position for a certain depth rotation and stops the spool at that memorized position.										
Power handle	 	●	● Big	●	●					
The power handle is a bigger handle for increased strength.										
Guard arm		●	●	●	●					
The guard arm is equipped as a standard option to prevent scratches on the body.										
Click sound brake system		●	●	●	●					
The sound brake system applies a slight brake to the spool and prevents backlash, and informs of the hit by the loud click sound.										
Electric linear drag						●				
Equipped with an electric lever drag lightly responds that driven by a sub motor.										
Backlight color change						●				
The LCD back light color can be chosen from 6 colors.										
High speed automatic winding							●			
High speed automatic winding function winds up at the highest speed to the zero stop position.										
Jigging		●	●	●	●		●		●	
Jigging (Jig up then pause then repeat) with one switch, and automatic winding up to the zero stop position. Customize Jig length, pause time, and number of jig cycle can be set or you can use a default setting.										
Auto Jigging								●		●
The auto jigging function automatically repeats the Jigging by letting the rig back out.										
Chumming								●		
The chumming function disperses bait from a certain shelf with a jigging motion and automatically repeats. Then winds up to the zero stop position.										
CE mark							●	● 12V		
CE marking indicates that the product conforms to the essential requirements specified in the EU directive and regulations by sector.										

MIYAMAE CO., LTD.

1-2-32 Aramoto Higashiosaka-Shi Osaka-Fu 577-0023 JAPAN

TEL+81-6-6782-1010 FAX+81-6-6782-1248

Notice: Modification, specification, and design are subject to change without notice.

Details and colors of the images might be different from ones of real products.

All descriptions are as of the issued date March 2022.