

COMMAND AC-3JP English Edition

AC-3JP English Edition is the technical model and installed with various functions in the most compact body. In addition to the main motor, the sub motor can control the drag. The sub motor makes possible the single switching operation called "Auto Clutch Function" (Clutch ON/OFF) .

Auto tension control

Depth memory

Auto Jigging

Chumming

CE

*Only the12V

Reel size / W215×H120×D150mm



COMMAND AC-3JPC English Edition

AC-3JPC English Edition is also available as a high-capacity spool model for AC-3JP En.

Auto tension control

Depth memory

Auto Jigging

Chumming

CE

Reel size / W215×H120×D150mm

AC-3JP/AC-3JPC English Edition

Item	Product Code	Drag Capacity	MAX Winding Power	Winding Power	MAX.Drag Winding Speed	Power Consumption	Gear Ratio	Line Capacity / When use Miya New Deep Sensor		Ball Bearing	Weight
AC-3JPEn (12V)	0255	30kg	43kg	16kg	150m/min	2.6-15A	1:1.92	No.4/ 700m	No.8/400m	10	2.1kg
AC-3JPEn (24V)	0256		50kg	24kg		1.3-12A		No.5/ 600m No.6/ 500m	No.10/300m No.12/200m		
AC-3JPCEn (12V)	0257	40kg	55kg	16kg	150m/min	2.6-15A	1:1.92	No.4/900m No.5/800m No.6/ 700m	No.8/550m No.10/450m No.12/350m	10	2.1kg

* Instruction manual is Japanese, and attached an explanatory leaflet in English.